



Mediatix[®] 4400 Series

The Mediatix 4400 Series features BRI gateways that can connect legacy PBX systems to cloud telephony services and IP PBX systems to PSTN landlines.

The Mediatix 4400 Series allows you to take advantage of the benefits of SIP based systems, while protecting the investment made in the existing telephony equipment.



Interconnects any device to SIP

The Mediatix 4400 Series links any digital connection to an IP network and delivers a rich feature set for a comprehensive VoIP solution.

PSTN access and legacy PBX system gateway

With configurable NT/TE BRI ports, local call switching, and user-defined call properties (including caller/calling ID), Mediatix 4400 Series gateways smoothly integrate into legacy PBXs and incumbent PSTN networks.

Highly reliable Fax and Modem Transmissions over IP

With T.38 and clear channel fax and modem pass-through capabilities, the Mediatix 4400 Series ensures seamless transport of voice and data services over IP networks.

Advanced Mass Management

Our advanced provisioning capabilities deliver remarkable benefits to Mediatix customers. Mediatix enables centralised CPE management, a definite advantage to monitor the network, ensure service, and reduce operational costs.

Mediatrix[®] 4400 Series

Applications

Operators

- ✓ Connect legacy equipment in PSTN replacement/TDM replacement projects
- ✓ Provide SIP termination for cloud telephony services
- ✓ Convert ISDN signaling to SIP for SIP trunking

System Integrators

- ✓ Integrate Unified Communications with legacy systems
- ✓ Connect Skype for Business with TDM trunks and legacy telephony equipment
- ✓ Keep existing telephony equipment in SIP migrations
- ✓ Inter-connect branch offices to headquarters

Key Features

Carrier-Grade Voice Quality

T.38 and clear channel fax over IP
High performance processing of up to 10 voice channels

Easy Configuration and Management

Zero-touch configuration
Intuitive Web GUI
Customisable factory settings

Robust Security

Encrypted media, signaling, and management
Deep packet inspection firewall with DoS protection

Networking

Dual-stack IPv6 and IPv4
Multiple IP addresses and VLANs
NAT, firewall, and router capabilities

Benefits

- ✓ High quality built and carrier-grade validation standards contribute to the industry's most reliable platform
- ✓ Extensive TR-069 support for an easy management of large-scale deployments with a centralised EMS
- ✓ Superior call routing and manipulation capabilities for the implementation of complex deployment scenarios

Technical Specifications

Media Processing

G.711 (A-law and μ -law), G.722, G.723.1a, G.726, and G.729a/b
G.168 echo cancellation
DTMF detection and generation
Carrier tone detection and generation
Silence detection/suppression and comfort noise
Configurable de-jitter buffer and packet length

IP Telephony Protocol

SIP (RFC 3261) over UDP, TCP, and TLS
IMS (3GPP TS 24.229)
RTP (RFC 3550)
SDP (RFC 4566)
Multi-part body support
Redundancy support via DNS SRV
Multiple trunk support
IPv4 and IPv6 dual stack signaling and media

Digital Telephony

Euro ISDN EDSS-1/ETSI BRI/NET3
ISDN speech, audio, and data (Fax Gr 4, UDI 64, and RDI 64)
ECMA-143 (QSIG-BC)
Advice of Charge AOC-D and AOC-E (ETS 300 182)
Power feeding for BRI phones (model dependent)

Call Routing

Local switching
Call filtering and blocking
Calling/called number manipulation using regular expressions
Routing criteria:

- Interface
- Calling/called party number
- Calling/called URI
- Time of day, day of week, and date
- Many others

Mapping and transformation of call properties to/from SIP headers
Hunt groups

Fax and Modem Support

Group 3/super G3 fax real-time fax over IP
T.38 fax relay (9.6 k and 14.4 k)
Clear channel (G.711) fax and modem pass-through

Enhanced Security

Denial of Service (DoS) protection
SIP over TLS
SRTP with AES cipher – 128 bits

MIKEY key management protocol (RFC 3830 and 4567)
SDES key management protocol (RFC 4568)
TLS-encrypted configuration and management
X.509 certificate management
OCSP (Online Certificate Status Protocol) revocation status verification
Supported TLS key exchange mechanism

- RSA
- Diffie-Hellman

Supported TLS ciphers (minimum):

- AES (128 and 256 bits)
- 3DES (168 bits)

Management

Zero-touch provisioning
TR-069, TR-104, and TR-111
Web GUI
SSH and TELNET
SNMP v1, v2c, and v3
Scripts/firmware files uploaded via HTTP, HTTPS, FTP, and TFTP
Multiple levels of management access rights
Customisable CDR
Event notifications via Syslog, SIP, log file, and SNMP traps
Remote activation of service licenses

Monitoring and Troubleshooting

Alarms and traps
Call Details Record (CDR)
Media quality statistics
System: CPU and memory usage
PCM capture
IP network capture
Diagnostic traces

Networking

IPv4 – IPv6
Multiple IP addresses per link or VLAN
Multiple VLANs per link
DHCP client
PPPoE (RFC 2516)
IEEE 802.1q + DSCP QoS tagging (media, signaling, and mgmt)
IEEE 802.1x wired authentication
LLDP-med (ANSI/TIA-1057)
QoS traffic shaping
Firewall with stateful inspection, rate-limitation, and automatic black-listing
Static routing
NAPT
DHCP Server

Quality of Service (QoS)

Bandwidth limitation and traffic shaping
TOS/DiffServ
IEEE 802.1p/Q
RTCP-XR – special order

Physical Interfaces

2 x 10/100 Base-T Ethernet RJ-45 connectors

Operating Environment

Operating temperature: 0°C to 45°C
Storage temperature: -20°C to 70°C
Humidity: up to 85%, non-condensing

Power Supply

External 100-240 VAC power supply

Dimensions

Height: 4.9 cm (1.9 in.) approx.
Width: 22 cm (8.7 in.) approx.
Depth: 17.6 cm (6.9 in.) approx.
Weight: 545 g (0.75 lb.) approx.



Mediatrix 4400 Series Models

Modèles	Téléphonie	Réseau
Mediatrix 4401	1 port BRI	2 ports ETH
Mediatrix 4402	2 ports BRI	2 ports ETH
Mediatrix 4404	4 ports BRI	2 ports ETH



A Trusted Partner

Media5 Corporation is a global supplier of multimedia communication solutions, offering a complete set of SIP-based products and technologies.

With a focus on innovation and excellence in customer support, we deliver highly adaptive hardware and software components as well as ready-to-market SoftClients. This allows our customers and partners to take advantage of secure, reliable, and comprehensive communication solutions.

Mediatrix access devices include a complete set of VoIP Adaptors, Media Gateways, and Session Border Controllers customer premise equipment to connect any network to cloud telephony services.

©2016 Media5 Corporation. Information is subject to change without notice. All rights reserved.

For additional information, contact your Media5 representative.

media5corp.com | sales@media5corp.com